

HVIS
High voltage insulation sheets
Voltage class 36 kV
Max. busbar width 150 mm

Product description

HVIS is an adhesive coated, heat-shrinkable sheet which provides insulation enhancement and protection against accidentally induced discharge. When heated the HVIS sheet shrinks in two directions to tightly conform to complex shapes. A Raychem void-filling mastic, S1061, can be added to ensure that even protruding shapes are insulated. A Raychem sealing mastic, S1085, can also be applied to provide an environmentally sealed connection. The sheet can be cut to size on site and loosely secured in place with clamps and brackets available from us. Once installed, the clamps and brackets can be removed and re-used. HVIS sheet will provide flashover protection up to 17.5 kV or up to 25 kV if the void-filling mastic is applied underneath the sheet, or up to 36 kV if a double layer of HVIS is used. Re-usable joint covers can also be made to allow access or maintenance when required.

Applications

HVIS sheet will cover almost any size or shape of busbar joint, making it ideal for insulating busbar tees, elbows and other connections where tubing and tape cannot be used.

Clearance reduction

The table below indicates the clearance reductions which are possible using HVIS sheet. These are derived from BIL, AC withstand, DC withstand and discharge extinction tests. These clearances should not be adopted without testing by the user. Sharp electrodes and unusual geometries may require wider clearances.



| Rated voltage (kV) | Phase - phase (mm) | Phase - ground (mm) | IEC 71-2 air clearance (mm) |
|----------------------------|--------------------|---------------------|-----------------------------|
| Round busbars | | | |
| 12 | 55 | 65 | 120 |
| 17.5 | 70 | 85 | 160 |
| 24 | 95 | 125 | 220 |
| 36 | 150 | 205 | 320 |
| Rectangular busbars | | | |
| 12 | 65 | 75 | 120 |
| 17.5 | 85 | 104 | 160 |
| 24 | 115 | 150 | 220 |
| 36 | 200 | 285 | 320 |

Features/benefits

- Compatible with all other products in the Raychem MV insulation enhancement system
- Easy to install on site using a gas torch or hot air device
- Manufactured from a non-halogen based material, noxious and corrosive effects are greatly reduced in the event of a fire
- Excellent anti-tracking properties
- Excellent UV and weather resistant properties make HVIS suitable for indoor or outdoor use
- Can be stored indefinitely at temperatures up to 50°C without loss of performance

HVIS


High voltage insulation sheets

| Key product specifications | Test method | Requirement |
|-------------------------------|------------------------|---------------------------------|
| Dielectric strength | ASTM D149, IEC 243 | 130 kV/cm min. @ 2 mm |
| Accelerated ageing | ISO 188, ASTM D2671 | 168 hrs @ 120°C |
| - Tensile strength | | 10 MPa min. |
| - Ultimate elongation | | 300% min. |
| Low temperature flexibility | ASTM D2671 Procedure C | No cracking after 4 hrs @ -40°C |
| Comparative tracking index | VDE 0303/1 | KA 3c |
| Smoke index | NES 711 | Less than 50 |
| Acid gas generation | Raychem PPS 3010 4.23 | Less than 2% by weight |
| Resistance to transformer oil | VDE 0370 | 168 hrs @ 23°C |
| - Tensile strength | | 7.5 MPa min. |
| - Ultimate elongation | | 300% min. |


Note: For further product specification information see Raychem PPS 3010/25. The above information refers to backing material only, for adhesive requirements see PPS 3012/43. For void-filling mastic S1061 requirements see PPS 3012/13, for sealing mastic S1085 requirements see PPS 3012/3.

Product selection

For rectangular busbars max. thickness 15 mm



T-connection





Flat elbow connection

| Busbar width | Cut size needed (mm) | No. of installations per sheet | | Cut size needed (mm) | No. of installations per sheet | |
|--------------|----------------------|--------------------------------|---------|----------------------|--------------------------------|---------|
| | | HVIS-05 | HVIS-10 | | HVIS-05 | HVIS-10 |
| 25 | 275 x 225 | 4 | 88 | 275 x 175 | 4 | 114 |
| 50 | 325 x 250 | 4 | 80 | 325 x 225 | 4 | 88 |
| 75 | 400 x 275 | 2 | 50 | 325 x 250 | 2 | 52 |
| 100 | 450 x 325 | 2 | 44 | 450 x 275 | 2 | 44 |
| 175 | 550 x 425 | 1 | 23 | 550 x 325 | 1 | 30 |

Note: This table should be used as a guideline only. Please experiment with one or two joints before adopting final cut size. The busbars are assumed to be insulated to 25 mm from the joint. Cut size should extend a minimum of 100 mm on each leg of the joint before shrinking and should overlap existing insulation by 65 mm after shrinking.

Ordering information



| Ordering description | Dimensions P a (m) nom. | Dimensions Q a nom. | W ₁ b min. | W ₂ a min. | UOM |
|--|-------------------------------|---------------------------|-----------------------------|-----------------------------|-------|
| HVIS-05 | 0.5 | 660 | 1.5 | 2.4 | sheet |
| HVIS-10 | 10.0 | 660 | 1.5 | 2.4 | roll |
| S1061-8-300 | 0.3 | 60 | - | - | piece |
| S1085-1-300 | 0.3 | 20 | - | - | piece |
| HVIS-TOOLS-01 (basic clamp and bracket kit) | | | | | kit |
| HVIS-TOOLS-02 (extended clamp and bracket kit) | | | | | kit |

Note: Dimensions in mm unless otherwise stated. a = as supplied b = after free recovery. Longitudinal and transverse change after free recovery: -25 % ±10%. Installation instructions EPP 0623 5/96 and Material Safety Data Sheet available on request. When required, typically one piece of sealing mastic, S1085, is applied on each leg of the joint and one or two pieces of void-filling mastic, S1061, used to cover uneven shapes.

Technical reports

UVR 8114 – Qualification report for HVIS

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct and reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance of any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for these products is set forth in our standard terms and conditions of sale. ALR, AMP, AXICOM, B&H, BOWTHORPE EMP, CROMPTON INSTRUMENTS, DORMAN SMITH, DULMISON, GURO, HELLSTERN, LA PRAIRIE, MORLYNN, RAYCHEM, and SIMEL are trademarks.



Energy Division – a pioneer in the development of economical solutions for the electrical power industry. Our product range includes: cable accessories, connectors & fittings, electrical equipment, instruments, lighting controls, insulators & insulation enhancement and surge arresters.



For more information and your country contact person, please visit us at:
<http://energy.tycoelectronics.com>



Tyco Electronics Raychem GmbH, Energy Division
Finsinger Feld 1, 85521 Ottobrunn/Munich, Germany
Phone: +49-89-6089-0, Fax: +49-89-6096345