



LOW VOLTAGE BUSHING COVERS LVBC

WILDLIFE AND ASSET PROTECTION PRODUCTS

KEY FEATURES

- Compatible with TE's Raychem LVIT, LVBT, BBIT, BPTM, HVBT and MVFT
- Flame retardant
- Operating temperature rating up to +105°C
- Easy to install and remove for inspection and maintenance

TE Connectivity's (TE) Raychem cold applied Low Voltage Bushing Covers LVBC are designed to protect and insulate energized bushings from flashover due to accidental contact up to 1 kV/2000A.

TE's Raychem LVBC can be used on low voltage bushings, on transformers, switchgears and substations. Our LVBC are hinged with push fit latches for easy cold applied fittings with easy for retro-fit installation and can be removed and reused.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.

Low Voltage Bushing Covers LVBC



TE's wildlife and asset protection products and systems of tubes, tapes, sheets, pre-formed covers and barriers provide a proven, cost-effective and easy-to-install solution to bird, animal and weather related outages.

PRODUCT PERFORMANCE		
Key Material Properties	Test Method	Required
		Low Voltage
Physical		
Resistance to Transformer Oil 1 68 hrs at 23°C	VDE 0370	Pass
Tensile Strength		11MPa min
Ultimate Elongation		300% min
Thermal Endurance	IEC 60216	105°C min
Flamability	ANSI C 37.20	60 seconds maximum
Color		Black
Electrical		
Dielectric Strength	ASTM D149	130 kV/cm min (2.5 mm)
Volume Resistivity	ASTM D257	1 x 10 ¹³ Ohm cm min

Note: The above information refers to the backing material only.

ORDERING INFORMATION		
Product Description	Bushing Size EN-50386 (Amps)	Pack Size
LVBC-DT3-250A (B12)	250	12
LVBC-DT-630/1250A (B12)	630	12
	1,000	
	1,250	
LVBC-DT3-2000A (B12)	2,000	12

TECHNICAL REPORT	
EDR-5499	LVBMOD Material Qualification Report

te.com/energy

© 2018 TE Connectivity. All Rights Reserved. EPP-3223-10/18-EN

Raychem, TE Connectivity and the TE connectivity (logo) are trademarks of the TE Connectivity Ltd. family of companies. Other logos, product and Company names mentioned herein may be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this brochure are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA:	+ 1 800 327 6996
Canada:	+ 1 (905) 475-6222
Mexico:	+ 52 (0) 55-1106-0800
Latin/S. America:	+ 54 (0) 11-4733-2200
France:	+ 33 380 583 200
UK:	+ 44 0870 870 7500
Germany:	+ 49 896 089 903
Spain:	+ 34 916 630 400
Italy:	+ 39 333 250 0915
Benelux:	+32 16 508 695
Russia:	+7 495-790 790 2-200
China:	+ 86 (0) 400-820-6015