

RIGID RED GUANO PROTECTION SHIELD (RRGS)

WILDLIFE AND ASSET PROTECTION PRODUCTS

KEY FEATURES

- Easy to install on insulator and bushings
- Bolted design for excellent mechanical hold and wind resistance
- Excellent insulator, prevention against phase-to-ground flashovers
- Rugged, non tracking, UV and chemical resistant polymer
- REACH and RoHS Compliant

TE Connectivity's (TE) Raychem Rigid Red Guano Shield (RRGS) protects against bird streamer caused outages. The unique shield design provides protection from fecal and other soluable contaminates coming from above the insulator string.

Fast and Versatile Installation

The RRGS two - piece shield design attaches easily with plastic bolts and nuts around the top of the insulator. TE manufactures designs for both porcelain, glass, polymeric and silicone insulator strings and available in both 450mm (18") and 600mm (24") diameter shield designs.

High Performance Material

Superior TE's Raychem high-voltage outdoor materials are used in the RRGS shield design. The rugged, non-tracking, UV-resistant, high temperature polymer ensures long-term performance even in extreme environmental conditions.

Customers can count on consistent, high quality products, driven by TE's proven innovation and backed by our extraordinary customer support.



Rigid Red Guano Protection Shield (RRGS)







TE's Wildlife and Asset Protection products and systems of tubes, tapes, sheets, pre-formed covers and barriers provide a proven, cost-effective and easy-to-install solution to bird, animal and weather related outages.





PRODUCT PERFORMANCE				
Physical				
Key Material Properties	Test Method	Required		
Tensile Strength	ASTM D2628	17 MPa min., 2450 psi min.		
Ultimate Elongation	ASTM D2628	25% min.		
Electrical				
Key Material Properties	Test Method	Required		
Tracking and Erosion	ASTM D2303	No tracking, erosion to top surface or flame. Stop Voltage Method Failure after 1 hr. at 2.5 kV 1 hr. at 2.75 kV 1 hr. at 3.0 kV Initiate at 2.5 kV and 20 min at 3.25 kV		
Selection				
Product Description	Insulator Type	Shield Diameter		
RRGS-35/470-FT (B12)	Polymeric/Silicone	450mm (18")		
RRGS-35/470-M (B12)	Porcelain/Glass	450mm (18")		
RRGS-35/600-FT (B3)	Polymeric/Silicone	600mm (24")		
RRGS-35/600-M (B3)	Porcelain/Glass	600mm (24")		

TECHNICAL REPO	CHNICAL REPORT	
EDR-5311	Rigid Red Barrier Board (RRBB) Product Qualification Report - RRGS Material Test Report	

INSTALLATION INSTRUCTIONS	
PII-56543	Installation Instructions for RRGS-35/470 and RRGS-35/600

te.com/energy

© 2018 TE Connectivity. All Rights Reserved. EPP-3180-DDS-8/18-Rigid-Red-Guano-Protection-Shield

TE Connectivity and TE connectivity (logo) are trademarks. Other logos, product and/or company names might be trademarks of their respective owners. While TE has made every reasonable effort to ensure the accuracy of the information in this brochure, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

FOR MORE INFORMATION: TE Technical Support Centers

USA: + 1800 327 6996 Canada: +1 (905) 475-6222 + 52 (0) 55-1106-0800 Mexico: Latin/S. America: + 54 (0) 11-4733-2200 France: + 33 380 583 200 UK: + 44 0870 870 7500 + 49 896 089 903 Germany: + 34 916 630 400 Spain: + 39 333 250 0915 Italy: Benelux: +32 16 508 695 Russia: +7 495-790 790 2-200 China: + 86 (0) 400-820-6015

